

Table 122.6.4 HSM Crash Distribution for Florida

Type Facility		Abbreviation	K	A	B	C	O	
Rural Roadways	2-lane Undivided	R2U	0.032	0.116	0.196	0.196	0.461	
	4-lane Undivided	R4U	0.029	0.111	0.182	0.219	0.460	
	4-lane Divided	R4D	0.030	0.112	0.206	0.197	0.453	
Urban & Suburban Arterials	2-lane Undivided	U2U	0.009	0.062	0.166	0.223	0.540	
	3-lane TWLTL	U32LT	N/A					
	4-lane Undivided	U4U	0.005	0.037	0.126	0.209	0.623	
	4-lane Divided	U4D	0.008	0.055	0.158	0.239	0.540	
	5-lane TWLTL	U52LT	N/A					
Freeways	Rural		0.019	0.081	0.165	0.177	0.558	
	Urban		0.006	0.043	0.131	0.216	0.604	
	Ramps		0.004	0.039	0.124	0.223	0.610	
All	All Roadways and Ramps		0.008	0.049	0.141	0.224	0.577	
Notes:		A - Incapacitating Injury	C - Possible (or minor) Injury					
		K – Fatality	B - Non-incapacitating Injury		O - Property Damage Only			

Tools and spreadsheets for use with these analytical methods have been developed and are available on the following websites:

<http://www.fdot.gov/safety/11A-SafetyEngineering/TransSafEng/HighwaySafetyManual.shtm>

<http://www.fdot.gov/roadway/QA/Tools.shtm>

